

HIGOLD®

Top-Mount Sink Installation Instructions

Follow these instructions if you are **top-mounting** your HIGOLD sink into a bench.


NOTE - All HIGOLD top-mount sink installations use these instructions. Therefore, images may differ from your sink model. Ensure your sink is in perfect condition before installation.

Installation Components


Description	Quantity
A Stainless steel sink	1
B Box of installation anchor clips	1
C Foam adhesive strip	1

Step 1 - Prepare benchtop

A template is provided or you can create one





Measure sink exterior from edge to edge in mm



Cut hole in benchtop

Step 2 - Insert Sink


Affix foam strip (optional)



Insert sink in the bench hole

Step 3 - Affix sink

Hook the anchor clips onto the sink's anchor points



Tighten the clips using a philip's head screwdriver in the order as shown in the supplied template

HIGOLD®

Under-Mount Sink Installation Instructions

Follow these instructions if you are **under-mounting** your HIGOLD sink into a bench.


NOTE - All HIGOLD under-mount sink installations use these instructions. Therefore, images may differ from your sink model. Ensure your sink is in perfect condition before installation.

Installation Components


Description	Quantity
A Stainless steel sink	1
B Box of hole plugs, anchor clips and bolts	1

Step 1 - Prepare benchtop

A template is provided or you can create one




Measure sink bowl interior in mm




Cut hole in benchtop as shown above. Match bench hole corner style to the sink, i.e. round corners for cornered sink

Step 2 - Prepare mounting holes

Look underneath bench hole. Measure and mark the mounting hole positions in the bench (refer to the supplied template)



Drill Ø10mm holes 15mm deep underneath bench as per supplied template




Plastic hole plug


Insert supplied plastic plugs into drilled mounting holes

Step 3 - Affix sink under bench

Position sink under bench in line with the hole



It is recommended that a suitable glass adhesive is applied when sink is positioned



Affix the sink firmly by fastening the clips and bolts into the mounting holes.

(Important: Refer to the supplied template for the order of affixing the clips)

HIGOLD®

Stainless Steel Handmade Sink

Installing the Strainer

Your strainer should be installed by a licensed plumber. Use the screw to tighten the main body (from underneath the sink) and the stainless steel strainer (from above the sink) into place. Sealants are not required. Install the basket on top of the strainer.



Stainless steel basket
Removable for cleaning and general use
Fixing screw



Stainless steel strainer
Insert in rubber seal



Rubber seal
Insert this into sink hole



Rubber gasket
Inserts in main drain body



Main drain body
Installed underneath sink hole
Plumber connects into plumbed drain

Care Instructions

HIGOLD stainless steel sinks are made from premium quality 304 stainless steel and applied with patented advanced coating to increase durability and resistance to high temperature and scratching.

Cleaning

- Clean the sink regularly with soapy warm water. Always rinse the sink after using cleaning products.
- Avoid solvents, alcohol, bleaching or acidic products, harsh chemicals and abrasives.
- Wipe the surface of the sink with a gentle cloth to remove liquid residue.
- Regularly clean the drain to prevent clogs and odors.

Care

- Do not cut food directly on the surface.
- Some foods after prolonged periods can damage the surface: e.g. foods and juices that contain acid or vinegar